

BBBBBBBBBBBB		00000000		00000000		TTTTTTTTTTTT		SSSSSSSSSS
BBBBBBBBBBBB		00000000		00000000		TTTTTTTTTTTT		SSSSSSSSSS
BBBBBBBBBBBB		00000000		00000000		TTTTTTTTTTTT		SSSSSSSSSS
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBBBBBBBBBBB		000	000	000	000	TTT	SSS	
BBBBBBBBBBBB		000	000	000	000	TTT	SSS	
BBBBBBBBBBBB		000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBB	BBB	000	000	000	000	TTT	SSS	
BBBBBBBBBBBB		00000000		00000000		TTT	SSSSSSSSSS	
BBBBBBBBBBBB		00000000		00000000		TTT	SSSSSSSSSS	
BBBBBBBBBBBB		00000000		00000000		TTT	SSSSSSSSSS	

```
BBBBBBBBB 000000 000000 TTTTTTTTTT DDDDDDDD RRRRRRRR IIIIII VV VV RRRRRRRR
BBBBBBBBB 000000 000000 TTTTTTTTTT DDDDDDDD RRRRRRRR IIIIII VV VV RRRRRRRR
BB BB 00 00 00 00 00 00 TT DD DD RR RR RR III II VV VV RR RR
BB BB 00 00 00 00 00 00 TT DD DD RR RR RR III II VV VV RR RR
BB BB 00 00 00 00 00 00 TT DD DD RR RR RR III II VV VV RR RR
BBBBBBBBB 00 00 00 00 00 00 TT DD DD RRRRRRRR III II VV VV RRRRRRRR
BBBBBBBBB 00 00 00 00 00 00 TT DD DD RRRRRRRR III II VV VV RRRRRRRR
BB BB 00 00 00 00 00 00 TT DD DD RR RR RR III II VV VV RR RR
BB BB 00 00 00 00 00 00 TT DD DD RR RR RR III II VV VV RR RR
BB BB 00 00 00 00 00 00 TT DD DD RR RR RR III II VV VV RR RR
BBBBBBBBB 000000 000000 TTT DDDDDDDD RRR RR RR IIIIII VV VV RR RR
BBBBBBBBB 000000 000000 TT DDDDDDDD RRR RR RR IIIIII VV VV RR RR
                                     ....
                                     ....
                                     ....
                                     ....

LL      IIIIII SSSSSSSS
LL      IIIIII SSSSSSSS
LL      II      SS
LL      II      SS
LL      II      SS
LL      II      SS
LL      II      SSSSSS
LL      II      SSSSSS
LL      II      SS
LL      II      SS
LL      II      SS
LL      II      SS
LLLLLLLLL IIIIII SSSSSSSS
LLLLLLLLL IIIIII SSSSSSSS
```



(2)	96	Declarations
(3)	141	DRIVER FIXED DATA AREA
(4)	228	BOO\$QIO - BOOTSTRAP QIO ROUTINE
(5)	462	BOO\$MAP - ROUTINE TO MAP DATA FOR BOO\$QIO
(6)	523	BOO\$PURDPR - Purge UBA Buffered Datapath
(8)	614	BOO\$SELECT - Select boot driver
(9)	650	BOO\$MOVE - Select and move boot driver

```

0000 1      .TITLE BOOTDRIVR DISPATCHER FOR BOOTSTRAP I/O DRIVERS
0000 2      .IDENT 'V04-000'
0000 3
0000 4
0000 5 *****
0000 6 *
0000 7 *  COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 8 *  DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 9 *  ALL RIGHTS RESERVED.
0000 10 *
0000 11 *  THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 12 *  ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 13 *  INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 14 *  COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 15 *  OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 16 *  TRANSFERRED.
0000 17 *
0000 18 *  THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 19 *  AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 20 *  CORPORATION.
0000 21 *
0000 22 *  DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 23 *  SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 24 *
0000 25 *
0000 26 *****
0000 27
0000 28 ++
0000 29
0000 30 FACILITY:
0000 31
0000 32 Minimal bootstrap driver for all VMS system disks.
0000 33
0000 34 ENVIRONMENT:
0000 35
0000 36 Runs at IPL 31, kernel mode, memory management may be on or off,
0000 37 IS=1 (running on interrupt stack), code must be PIC.
0000 38
0000 39 ABSTRACT:
0000 40
0000 41 This module contains a routine called BOO$QIO that handles I/O
0000 42 transfers to and from the VMS system disks.
0000 43
0000 44 AUTHOR:
0000 45
0000 46 The VMS group
0000 47
0000 48 REVISION HISTORY:
0000 49
0000 50 V03-011 TCM0005 Trudy C. Matthews 24-Jul-1984
0000 51 Bump the VMB version number to indicate that the field
0000 52 RPB$B_CTRLTR is now being initialized.
0000 53
0000 54 V03-010 KPL0101 Peter Lieberwirth 11-Apr-1984
0000 55 Update VMB version number for word-sized RPB field. This
0000 56 should have been done as part of v03-009.
0000 57

```



0000	58	:	V03-009	KPL0100	Peter Lieberwirth	12-Feb-1984
0000	59	:		Change use of RPB\$B_BOOTNDT to RPB\$W_BOOTNDT, since BI		
0000	60	:		devices will have 16-bit device types.		
0000	61	:				
0000	62	:	V03-008	KDM0084	Kathleen D. Morse	23-Sep-1983
0000	63	:		Add Micro-VAX I to CPUDISP.		
0000	64	:				
0000	65	:	V03-007	KDM0073	Kathleen D. Morse	22-Aug-1983
0000	66	:		Add EXE\$GL_TENUSEC and EXE\$GL_UBDELAY to the fixed		
0000	67	:		data cells used by the bootstrap drivers. Create		
0000	68	:		BQO symbols for these data cells.		
0000	69	:				
0000	70	:	V03-006	TCM0004	Trudy C. Matthews	02-Aug-1983
0000	71	:		Add definition for EXE\$GB_CPUDATA cell.		
0000	72	:				
0000	73	:	V03-005	KTA3059	Kerbey T. Altmann	21-Jun-1983
0000	74	:		Add entries for unit disconnect and boot device name -		
0000	75	:		thus bumping VMB version number.		
0000	76	:				
0000	77	:	V03-004	RLRCPUDISP	Robert L. Rappaport	15-Jun-1983
0000	78	:		Recode CPUDISP macros to use new format.		
0000	79	:				
0000	80	:	V03-003	TCM0003	Trudy C. Matthews	23-Feb-1983
0000	81	:		Increment VMB version number to indicate adding RPB\$L_BADPGS		
0000	82	:		field.		
0000	83	:				
0000	84	:	V03-002	TCM0002	Trudy C. Matthews	05-Jan-1983
0000	85	:		Add 11/790-specific path to BOO\$PURDPR.		
0000	86	:				
0000	87	:	V03-001	KTA0092	Kerbey T. Altmann	02-Apr-1982
0000	88	:		Bump the version number because of KTA0090.		
0000	89	:				
0000	90	:	V02-021	KTA0090	Kerbey T. Altmann	26-Mar-1982
0000	91	:		Add new cell to IOVEC to contain address of microcode		
0000	92	:		required by a booting device.		
0000	93	:				
0000	94	---				



```

0000 96          .SBTTL Declarations
0000 97
0000 98  :
0000 99  : MACRO LIBRARY CALLS
0000 100 :
0000 101
0000 102          $BQODEF          : Define boot qio offsets
0000 103          $BTDDDEF         : Define boot device types
0000 104          $IODEF           : DEFINE I/O FUNCTION CODES
0000 105          $MBADEF          : DEFINE MASSBUS ADAPTER REGISTERS
0000 106          $NDTDEF          : NEXUS device types
0000 107          $PRDEF           : DEFINE PROCESSOR REGISTERS
0000 108          $PTDEF           : DEFINE PAGE TABLE ENTRY FIELDS
0000 109          $RPBDEF          : DEFINE RESTART PARAMETER BLOCK
0000 110          $SSDEF           : DEFINE STATUS CODES
0000 111          $UBADEF          : UNIBUS ADAPTER REGISTER DEFINITIONS
0000 112          $UBIDEF          : 11/750 UNIBUS adapter regs.
0000 113          $VADEF           : DEFINE VIRTUAL ADDRESS FIELDS
0000 114
0000 115  :
0000 116  : MACROS
0000 117  :
0000 118
0000 119  :
0000 120  : LOCAL SYMBOLS
0000 121  :
0000 122
0000 123          $DEFINI BDT          : Define Boot Driver Table offsets
0000 124
0000 125 $DEF      BDT$$_CPU$$_TYPE  .BLKW 1          : CPU type
0002 126 $DEF      BDT$$_DEV$$_TYPE .BLKW 1          : Boot R0 device type
0004 127 $DEF      BDT$$_ACT$$_ION   .BLKL 1          : Action routine
0008 128 $DEF      BDT$$_S$$_IZE     .BLKL 1          : Driver size
000C 129 $DEF      BDT$$_ADD$$_R     .BLKL 1          : Driver address (offset)
0010 130 $DEF      BDT$$_ENT$$_RY    .BLKL 1          : Driver entry (offset from address)
0014 131 $DEF      BDT$$_DRIV$$_NAME .BLKL 1          : Driver name (offset from address)
0018 132 $DEF      BDT$$_AUX$$_DRNAME .BLKL 1          : Auxiliary driver name (offset)
001C 133 $DEF      BDT$$_UNIT$$_INIT .BLKL 1          : Driver unit init (offset from address)
0020 134 $DEF      BDT$$_UNIT$$_DISC .BLKL 1          : Driver unit disc (offset from address)
0024 135 $DEF      BDT$$_DEV$$_NAME  .BLKL 1          : Device name (offset from address)
0028 136
00000028 0028 137 BDT$$_K$$_LENGTH=.          : Length of entry
0028 138
0028 139          $DEFEND BDT          : End of Boot Driver Table definitions

```



```

0000 141 .SBTTL DRIVER FIXED DATA AREA
0000 142
0000 143 :
0000 144 :
0000 145 :
0000 146 :
00000000 147 .PSECT BOOTDRIVR_1, LONG ; CERTAIN DRIVERS REQUIRE ALIGNMENT!
0000 148
0000 149 BOOSAL_VECTOR:: ; VECTOR TO BOOT DRIVER ENTRY POINTS
00000046' 0000 150 .LONG BOOSQIO-BOOSAL_VECTOR ; OFFSET TO BOOTSTRAP QIO ROUTINE
0000011D' 0004 151 .LONG BOOSMAP-BOOSAL_VECTOR ; OFFSET TO MAPPING ROUTINE
00000000' 0008 152 .LONG BOOSSELECT-BOOSAL_VECTOR ; OFFSET TO BOOTSTRAP I/O DRIVER
000C 153 ; INITIALLY SET TO ROUTINE WHICH
000C 154 ; SELECTS DRIVER
00000000 000C 155 .LONG 0 ; OFFSET TO SYSTEM DISK DRIVER NAME
0010 156 ; (ASCII STRING). SET UP BY BOOT DRIVER.
0010 157 :
0010 158 : The next two words are the version number and the version number check fields.
0010 159 : (The second word is the ones complement of the first word.) The version
0010 160 : number should be incremented whenever the interface between VMB and the
0010 161 : rest of the system changes. Release 1.0 VMB did not contain these fields.
0010 162 :
0010 163 : Version 2 - Boot driver passes system disk driver name to SYSBOOT
0010 164 : Version 3 - VMB build memory description vector into RPB
0010 165 : Version 4 - VMB BOOTDRIVR purges UBA buffered datapath, all drivers
0010 166 : return to BOOTDRIVR with success/failure status
0010 167 : Version 5 - VMB passes an argument list to the secondary boot
0010 168 : in AP. FILEREAD cacheing is present.
0010 169 : Version 6 - VMB passes nexus device type of boot adapter in
0010 170 : RPB$B BOOTNDT.
0010 171 : Version 7 - BOOSAL_VECTOR now has new entry points for RESELECTing
0010 172 : a driver and UNIT_INIT for a driver. Also new info
0010 173 : passed in the argument list.
0010 174 : Version 8 - BOOSAL_VECTOR now has a new cell: BOOSL_UCODE.
0010 175 : Version 9 - VMB passes number of bad memory pages found during
0010 176 : bootstrap scan in RPB$B BADPGS.
0010 177 : Version 10- BOOSAL_VECTOR has two new cells: UNIT_DISC and DEVNAME
0010 178 :
0010 179 : Version 11- BOOSAL_VECTOR has two new cells: TENUSEC and UBDELAY
0010 180 :
0010 181 : Version 12- RPB$B BOOTNDT is defined, high byte of this word must
0010 182 : be cleared in SYSBOOT for versions of VMB less than 12.
0010 183 :
0010 184 : Version 13- RPB$B CTRLLTR is defined; SYSBOOT must clear this field
0010 185 : for older versions of VMB.
0010 186 :
0010 187 :
0000000D 0010 188 VMB_VERSION = 13
0010 189
0010 190 ASSUME <.-BOOSAL_VECTOR> EQ BOOSW_VERSION
FFF2 000D 0010 191 .WORD VMB_VERSION, ^C<VMB_VERSION> ; VERSION # AND VERSION # CHECK FIELD.
00000063' 0014 192 .LONG BOOSRESELECT-BOOSAL_VECTOR ; Offset to set new driver
00000012' 0018 193 .LONG BOOSMOVE-BOOSAL_VECTOR ; Offset to routine to select and move
001C 194 ASSUME <.-BOOSAL_VECTOR> EQ BOOSL_UNIT_INIT
00000000 001C 195 .LONG 0 ; Offset to UNIT_INIT
0020 196 ASSUME <.-BOOSAL_VECTOR> EQ BOOSL_AUXDRNAME
00000000 0020 197 .LONG 0 ; Offset to auxiliary driver name

```

```

0024 198 ; second driver
0024 199 ASSUME <.-BOOSAL_VECTOR> EQ BQOSL_UMR_DIS
0024 200 BOOSGL_UMR_DIS:: ; Number of map registers disabled
00000000 0024 201 .LONG 0
0028 202 ASSUME <.-BOOSAL_VECTOR> EQ BQOSL_UCODE
00000000 0028 203 BOOSGL_UCODE:: ; Address of microcode in memory
0028 204 .LONG 0
002C 205 ASSUME <.-BOOSAL_VECTOR> EQ BQOSL_UNIT_DISC
00000000 002C 206 .LONG 0 ; Offset to UNIT_DISC
0030 207 ASSUME <.-BOOSAL_VECTOR> EQ BQOSL_DEVNAME
00000000 0030 208 .LONG 0 ; Offset to boot device name
0034 209 ASSUME <.-BOOSAL_VECTOR> EQ BQOSL_UMR_TMPL
0034 210 BOOSGL_UMR_TMPL:: ; ONIBUS map register template
80000000 0034 211 .LONG UBASM_MAP_VALID ; Default is valid, no buff data path
0038 212 ASSUME <.-BOOSAL_VECTOR> EQ BQOSB_UMR_DP
0038 213 BOOSGB_UMR_DP:: ; ONIBUS map register data path
01 0038 214 .BYTE 1 ; Default is Buffered #1
0039 215 ASSUME <.-BOOSAL_VECTOR> EQ BQOSB_CPUTYPE
0039 216 EXESGB_CPUTYPE:: ; Location to hold processor
01 0039 217 .BYTE 1 ; identification code
003A 218 ASSUME <.-BOOSAL_VECTOR> EQ BQOSL_CPUDATA
003A 219 EXESGB_CPUDATA:: ; Location to hold contents of SID.
00000001 003A 220 .LONG 1
003E 221 ASSUME <.-BOOSAL_VECTOR> EQ BQOSL_TENUSEC
00000001 003E 222 EXESGL_TENUSEC:: ; Location to hold TIMEDWAIT delay count
003E 223 .LONG 1
0042 224 ASSUME <.-BOOSAL_VECTOR> EQ BQOSL_UBDELAY
00000001 0042 225 EXESGL_UBDELAY:: ; Location to hold TIMEDWAIT delay count
0042 226 .LONG 1

```



```

0046 228      .SBTTL BOO$QIO - BOOTSTRAP QIO ROUTINE
0046 229
0046 230      :++
0046 231      : FUNCTIONAL DESCRIPTION:
0046 232      :
0046 233      : BOO$QIO PROVIDES THE DEVICE INDEPENDENT I/O INTERFACE FOR BOTH
0046 234      : READING AND WRITING THE BOOTSTRAP DEVICE.
0046 235      :
0046 236      : CALLING SEQUENCE:
0046 237      :
0046 238      : CALLG  ARGLIST,BOO$QIO
0046 239      :
0046 240      : INPUT PARAMETERS:
0046 241      :
0046 242      : BUF(AP) - BUFFER ADDRESS
0046 243      : SIZE(AP) - SIZE OF BUFFER IN BYTES
0046 244      : LBN(AP) - LOGICAL BLOCK NUMBER
0046 245      : FUNC(AP) - FUNCTION CODE
0046 246      :                      ACCEPTS IOS_READBLK AND IOS_WRITEBLK
0046 247      : MODE(AP) - ADDRESS INTERPRETATION MODE
0046 248      :                      0 => PHYSICAL, 1 => VIRTUAL
0046 249      : RPB(AP) - ADDRESS OF RESTART PARAMETER BLOCK
0046 250      :
0046 251      : OUTPUT PARAMETERS:
0046 252      :
0046 253      : R0 - COMPLETION STATUS CODE
0046 254      : R1 - TOTAL BYTES TRANSFERRED
0046 255      :
0046 256      :--
0046 257
0046 258      :
0046 259      : Offsets from AP to input arguments:
0046 260      :
0046 261      :
00000004 0046 262      BUF      = 4
00000008 0046 263      SIZE     = 8
0000000C 0046 264      LBN      = 12
00000010 0046 265      FUNC     = 16
00000014 0046 266      MODE     = 20
00000018 0046 267      RPB      = 24
0046 268
0046 269 BOO$QIO::
OFFC 0046 270      .WORD  ^M<R2,R3,R4,R5,R6,R7,- ; PRESERVE REGISTERS
0048 271      R8,R9,R10,R11>
0048 272
0048 273      :
0048 274      : If mapping is enabled, the processor register RPS_MAPEN contains a 1.
0048 275      : Otherwise, the register contains a 0. Use this value as an index to
0048 276      : choose the appropriate address of the adapter's register space.
0048 277      :
0048 278
59 18 AC DO 0048 279      MOVL  RPB(AP),R9 ; GET BASE ADDRESS OF RESTART PARAMETER BLK
51 38 DB 004C 280      MFPR  #PRS_MAPEN,R1 ; CHECK FOR MAPPING ENABLED
004F 281      ASSUME RPB$C_ADPPVIR EQ RPB$L_ADPPHY+4
53 5C A941 DO 004F 282      MOVL  RPB$L_ADPPHY(R9)[R1],R3 ; GET CORRECT POINTER TO CONFIG REG
0054 283
0054 284 ;

```

```

0054 285 : Using the argument list as input, calculate the transfer size, number
0054 286 : of map registers, starting LBN, starting VPN, and base of a page table
0054 287 : to use in mapping.
0054 288 :
0054 289 :
5A 04 AC D0 0054 290      MOVL    BUF(AP),R10      : Get buffer address
58 08 AC 3C 0058 291      MOVZWL  SIZE(AP),R8      : GET TRANSFER SIZE IN BYTES
                                10$      : CONTINUE IF LEGAL SIZE
58 01 10 9C 005E 292      ROTL     #16,#1,R8      : ELSE FORCE TO 64K SIZE
57 5A 09 00 EF 0062 293 10$: EXTZV    #VASV_BYTE,#VASS_BYTE,R10,R7 : Get byte offset into page
57 03FF C847 9E 0067 294      MOVAB   ^X3FF(R8)(R7),R7 : Calculate highest address plus
                                : an overflow page.
57 57 F7 8F 78 006D 295      ASHL     #-9,R7,R7      : Reduce to number of pages
                                : (= number of map registers).
                                : AND BLOCK NUMBER FOR RETRY
5B 0C AC D0 0072 296      MOVL     LBN(AP),R11      : ASSUME SYSTEM SPACE
51 50 A9 D0 0076 297      MOVL     RPB$S_SVASPT(R9),R1 : Branch if system address
03 5A 1F E0 007A 300      BBS       #VASV_SYSTEM,R10,20$ : OTHERWISE GET PO PT BASE
52 5A 15 08 DB 007E 301 20$: MFPR     #PRS_POBR,R1      : Get base VPN for transfer
                                : If booting from console block
                                : storage device or CI,
                                : don't load map registers
                                :
                                : Register usage right now is as follows:
008C 302      R1          - address of page table for virtual-->physical mapping
008C 303      R2          - base VPN for the transfer
008C 304      R3          - address of the adapter's configuration register
008C 305      R7          - number of map registers needed (plus one extra)
008C 306      R8          - transfer size in bytes
008C 307      R9          - address of the RPB
008C 308      R10         - buffer address
008C 309      R11         - starting LBN of the transfer
008C 310 :
008C 311 : In an adapter-dependent fashion, initialize the required number of
008C 312 : adapter map registers. First calculate the address of the starting map
008C 313 : register number. Right now, map registers for all UNIBUS and MASSBUS
008C 314 : adapters for all processors start at the same offset from the base of
008C 315 : the adapter's register space.
008C 316 :
008C 317 : During map register initialization, the following registers change
008C 318 : for each page mapped:
008C 319 :
008C 320      R2          - address of the next VPN to map
008C 321      R4          - address of the next map register to load
008C 322      R5          - PFN of the page being mapped
008C 323 :
008C 324 :
008C 325 :
008C 326 :
008C 327 :
008C 328 :
008C 329 :
008C 330 :
008C 331 :
008C 332 :
008C 333 :
008C 334 INIT_MAPREGS: : Initialize the map registers.
008C 335      ASSUME     MBASL_MAP EQ UBASL_MAP
008C 336      ASSUME     MBASL_MAP EQ UBISL_MAP
54 FF94 CF D0 008C 337      MOVL     W^BOOSGL_UMR_DIS,R4 : Pick up number of disable UMR's
54 0800 C344 DE 0091 338      MOVAL   MBASL_MAP(R3)(R4),R4 : Point to first useable map register
                                :
0097 339 :
0097 340 COMPUTE_PFN: : Loop once per page.
0097 341      MOVAB    (R2)+,R5      : Get a virtual page number.

```



```

      OB 14 AC      E9 009A 342      BLBC  MODE(AP),10$      ; If physical page #, branch.
      55 55 6145    D0 009E 343      MOVL  (R1)[R5],R5      ; Get page table entry
      FFE00000 8F  CA 00A2 344      BICL  #^C<PTESM_PFN>,R5      ; and extract PFN from entry
      00A9 345
      00A9 346
      00A9 347      ; Derive the boot device adapter's type (UNIBUS adapter or MASSBUS
      00A9 348      ; adapter) from the RPB, and save a flag indicating the adapter type
      00A9 349      ; in a register. The seemingly complicated fooling around with both
      00A9 350      ; a UMR_DP and UMR_TMPL is to allow flexibility in what devices desire
      00A9 351      ; in the way of data paths: Only UNIBUS devices will ever even pick up
      00A9 352      ; the UMR_DP bit. Thus all non-UNIBUS boot devices will never purge
      00A9 353      ; a data path. UNIBUS devices have a choice: by clearing UMR_DP in
      00A9 354      ; their UNIT_INIT routines, the boot drivers can elect to not use
      00A9 355      ; the buffered data path.
      00A9 356
      00A9 357
      56 00A1 50      D4 00A9 358 10$:  CLRL  R0      ; Assume not UNIBUS
      56 03 3C      3C 00AB 359      MOVZWL RPB$W_BOOTNDT(R9),R6      ; Pick up nexus type of boot adapter
      28 56 03      CA 00B0 360      BICL  #3,R6      ; Make canonical adapter type
      11 56 03      B1 00B3 361      CMPW  R6,#NDT$_UB0      ; If boot adapter is a UNIBUS,
      50 12      D6 00B6 362      BNEQ  20$      ; then
      FF7A CF      F0 00BA 363      INCL  R0      ; Set a flag for later user
      02 15      00BE 364      INSV  BOO$GB_UMR_DP,-      ; Pick up the data path
      FF71 CF      00C0 365      #UBA$V_MAP_DPD,#2,-      ; and put it in the template
      00C3 366
      00C3 367
      00C3 368      ; This is a UNIBUS adapter.
      00C3 369
      00C3 370      ; Map registers for the UNIBUS adapter look like the following:
      00C3 371
      00C3 372      ; -----+
      00C3 373      ; | V | | BO | DP # | | page frame number |
      00C3 374      ; -----+
      00C3 375
      00C3 376
      00C3 377      ; The code sets the byte offset bit if relevant, sets the valid bit,
      00C3 378      ; sets the low bit in the 4-bit data path field to indicate that the
      00C3 379      ; first buffered data path is to be used (if selected), and loads the
      00C3 380      ; page frame number into the low bits.
      00C3 381
      00C3 382
      19 04 AC      F0 00C3 383      INSV  BUF(AP),#UBA$V_MAP_BO,- ; Set UBA byte offset bit if
      55 01 01      00C7 384      #1,R5      ; necessary.
      00C9 385
      00C9 386      ; ***** NOTE ***** For most devices, always uses Datapath #1,
      00C9 387      ; IOC$PURDPR depends on this!!
      00C9 388
      84 FF66 CF      55  C9 00C9 389 20$:  BISL3  R5,BOO$GL_UMR_TMPL,(R4)+; Set PFN and byte offset, valid bit,
      00CF 390      ; and buffered DP number into map.
      00CF 391
      00CF 392      ; This is a MASSBUS adapter.
      00CF 393
      00CF 394      ; MASSBUS adapter's map registers look like the following:
      00CF 395
      00CF 396      ; -----+
      00CF 397      ; | V | | | | page frame number |
      00CF 398      ; -----+

```

```

00CF 399 :
00CF 400 :
00CF 401 : *****
00CF 402 : BISL3 R5,#MBASM_MAP_VALID,- ; Set the PFN and the valid bit
00CF 403 : (R4)+ ; in the map register.
00CF 404 : *****
00CF 405 :
00CF 406 : ; Is there another page to do?
57 D7 00CF 407 : DECL R7 ; Decrement # of map registers.
C4 14 00D1 408 : BGTR COMPUTE_PFN ; Loop to fill next map register
00D3 409 : ; if byte count not exhausted.
00D3 410 :
00D3 411 :
00D3 412 : All map registers are set up. Set up 2 more inputs to driver code.
00D3 413 : Since the loaded MBA map registers are registers #0-n, the starting
00D3 414 : address of the transfer to be loaded into a device register by the
00D3 415 : device driver, is now simply the offset into the first page of the
00D3 416 : transfer buffer. However, for the UBA, there may be some disabled
00D3 417 : map registers as a result of UNIBUS memory on the UBA. Therefor,
00D3 418 : the starting address of the transfer must include the lowest enabled
00D3 419 : UMR in bits 9-17.
00D3 420 :
00D3 421 :
09 00 EF 00D3 422 : EXTZV #VASV_BYTE,#VASS_BYTE,- ; Get byte offset into page
5A 5A 00D6 423 : R10,R10 ; in R10
00D8 424 :
00D8 425 :
00D8 426 : Invalidate the last UBA map register so that a wild transfer will stop
00D8 427 : at the end of the last valid block. Get the proper UMR to start with.
00D8 428 :
00D8 429 :
74 10 50 E9 00D8 430 : BLBC R0,30$ ; Skip invalidation for MBA.
50 80000000 8F CA 00DB 431 : BICL #UBASM_MAP_VALID,-(R4) ; Invalidate last map register.
FF3D CF 09 9C 00E2 432 : ROTL #9,#BOOSGL_UMR_DIS,R0 ; Form UNIBUS address of UMR
5A 50 C8 00E8 433 : BISL R0,R10 ; Set into address register.
00EB 434 :
00EB 435 :
00EB 436 : If it is a UNIBUS boot device, derive the address of the device's CSR.
00EB 437 :
00EB 438 :
00EB 439 : ASSUME RPB$$_CSRVR EQ RPB$$_CSRPHY+4
00EB 440 :
57 50 38 DB 00EB 441 30$: MFPR #PR$ MAPEN,R0 ; Check for mapping enabled
54 A940 DO 00EE 442 : MOVL RPB$$_CSRPHY(R9)[R0],R7 ; Get address of device's CSR
00F3 443 :
00F3 444 : PUSH_RETRY:
00F3 445 : PUSHL #10 ; Push retry count on stack
00F5 446 :
55 5B DO 00F5 447 10$: MOVL R11,R5 ; Get a working copy of the block number
50 34 A9 DO 00F8 448 : MOVL RPB$$_IOVEC(R9),R0 ; Get address of boot vectors
08 B040 16 00FC 449 : JSB @BQOS$_SELECT(R0)[R0] ; Call driver thru self-relative vector
15 E1 0100 450 : BBC #UBASV_MAP_DPD,- ; Branch if not using the Buffered
10 FF2F CF 0102 451 : BOOSGL_UMR_TMPL,100$ ; data path
50 DD 0106 452 : PUSHL R0 ; Save driver status
006A 30 0108 453 : BSBW BOOSPURDPR ; Purge Buffered Datapath for UBA
05 50 E8 010B 454 : BLBS R0,80$ ; Branch if success
5E 04 C0 010E 455 : ADDL #4,SP ; Clear previous status from stack

```



BOOTDRIVR  
V04-000

DISPATCHER FOR BOOTSTRAP I/O DRIVERS<sup>J 4</sup>  
BOOSQIO - BOOTSTRAP QIO ROUTINE

15-SEP-1984 23:40:28 VAX/VMS Macro V04-00  
4-SEP-1984 23:02:48 [BOOTS.SRC]BOOTDRIVR.MAR;1

Page 10  
(4)

06	11	0111	456	BRB	150\$
50	8ED0	0113	457 80\$:	POPL	R0
03 50	E8	0116	458 100\$:	BLBS	R0,200\$
D9 6E	F5	0119	459 150\$:	SOBGTR	(SP),10\$
	04	011C	460 200\$:	RET	

: Retry  
: Get driver status back  
: Branch if success  
: Retry if count > 0  
: Return with final status in R0

```

011D 462 .SBTTL BOOSMAP - ROUTINE TO MAP DATA FOR BOOSQIO
011D 463
011D 464 :++
011D 465 : FUNCTIONAL DESCRIPTION:
011D 466 : BOOSMAP IS CALLED TO INITIALIZE THE DATA BASE FOR BOOSQIO TO PERMIT
011D 467 : IT TO FUNCTION WITH MEMORY MANAGEMENT ENABLED. AN AREA OF SYSTEM
011D 468 : PAGE TABLE MUST BE PROVIDED SO THAT THE CONFIGURATION REGISTERS AND
011D 469 : UNIBUS I/O PAGE CAN BE MAPPED.
011D 470
011D 471 : CALLING SEQUENCE:
011D 472 : CALLG  ARGLIST,BOOSMAP
011D 473
011D 474 : INPUT PARAMETERS:
011D 475 : SVASPT(AP) - SYSTEM VIRTUAL ADDRESS OF THE SYSTEM PAGE TABLE
011D 476 : SVASPT = 4
011D 477 : VABASE(AP) - BASE VIRTUAL ADDRESS OF A 24 PAGE WINDOW TO MAP
011D 478 : THE ADAPTER CONFIGURATION REGISTERS AND UNIBUS
011D 479 : VABASE = 8
011D 480 : I/O PAGE.
011D 481 : RPB(AP) - ADDRESS OF RESTART PARAMETER BLOCK (RPB) CONTAINING
011D 482 : BOOTSTRAP DEVICE DESCRIPTION.
011D 483 : RPB = 12
011D 484
011D 485 : OUTPUT PARAMETERS:
011D 486 : NONE
011D 487
011D 488 :--
011D 489
011D 490 BOOSMAP: .WORD ^M<R2,R3,R4,R5,R6,R7>
011F 491 MOVL RPB(AP),R7 ; GET BASE ADDRESS FOR RPB
0123 492 MOVL SVASPT(AP),R2 ; GET BASE OF SPT
0127 493 MOVL R2,RPB$S SVASPT(R7) ; AND SAVE IN DATA BASE
012B 494 MOVL VABASE(AP),R3 ; GET VIRTUAL ADDRESS OF WINDOW
012F 495 MOVL R3,RPB$S ADPVIR(R7) ; SET AS ADAPTER VIRTUAL ADDRESS
54 5C A7 15 09 EF 0133 496 EXTZV #VASV_VPN,#VASS_VPN,RPB$S ADPPHY(R7),R4 ; GET BASE PFN
50 53 15 09 EF 0139 497 MOVL #8,R5 ; SET TO MAP 8 PAGES
51 6240 DE 0141 498 EXTZV #VASV_VPN,#VASS_VPN,R3,R0 ; GET BASE VIRTUAL PAGE
55 10 DO 0145 499 MOVAL (R2)[R0],R1 ; COMPUTE WORKING SPT POINTER
54 54 A7 00001FFF 8F CB 014A 500 BSBB FILLSP ; FILL SPT TO MAP CONFIGURATION REGS
54 54 17 9C 0153 501 MOVL #16,R5 ; SET FOR 16 PAGES
58 A7 FFFF3000 E043 3C 0157 502 BICL3 #^X1FFF,RPB$S_CSRPHY(R7),R4 ; GET PHY ADDR OF I/O PAGE BASE
50 54 A7 00001FFF 8F CB 0153 503 ROTL #<32-9>,R4,R4 ; AND CONVERT TO PAGE NUMBER
50 54 A7 00001FFF 8F CB 0157 504 BSBB FILLSP ; STORE PTES INTO SPT
58 A7 FFFF3000 E043 3C 0159 505 MOVZWL RPB$S_CSRPHY(R7),R0 ; GET I/O PAGE OFFSET
50 54 A7 00001FFF 8F CB 015D 506 MOVAB <^X1000-^XE000>(R0)[R3],RPB$S_CSRVIR(R7) ; SET VIRTUAL CSR ADDR
50 54 A7 00001FFF 8F CB 0166 507 RET
0167 508
0167 509 :++
0167 510 : FILLSP
0167 511
0167 512 : INPUTS:
0167 513 : R1 - POINTER TO CURRENT SPT ENTRY (UPDATED)
0167 514 : R4 - PFN (UPDATED)
0167 515 : R5 - COUNT OF PAGES TO FILL (UPDATED)
0167 516
0167 517 FILLSP:
81 54 90000000 8F C9 0167 518 BISL3 #<PTESM_VALID!PTESC_KW>,R4,(R1)+ ; STORE A PTE

```



BOOTDRIVR  
V04-000

DISPATCHER FOR BOOTSTRAP I/O DRIVERS<sup>L 4</sup>  
BOOSMAP - ROUTINE TO MAP DATA FOR BOOSQI

15-SEP-1984 23:40:28  
4-SEP-1984 23:02:48

VAX/VMS Macro V04-00  
[BOOTS.SRC]BOOTDRIVR.MAR;1

Page 12  
(5)

F3 54 D6 016F 519  
55 F5 0171 520  
05 0174 521

INCL R4  
SOBGTR R5,FILLSPT  
RSB

; ADVANCE TO NEXT PFN  
; STORE THEM ALL

```

0175 523 .SBTTL BOOS$PURDPR - Purge UBA Buffered Datapath
0175 524
0175 525 :++
0175 526 : FUNCTIONAL DESCRIPTION:
0175 527 :
0175 528 : This routine is called by BOOTDRIVR at the end of each boot device
0175 529 : transfer if the boot device is on the Unibus. It purges the buffered
0175 530 : datapath and/or performs other Unibus adapter specific end-action.
0175 531 :
0175 532 : NOTE: This routine contains processor specific code.
0175 533 :
0175 534 : CALLING SEQUENCE:
0175 535 :
0175 536 : JSB BOOS$PURDPR
0175 537 :
0175 538 : INPUT PARAMETERS:
0175 539 :
0175 540 : R3 - Address of UBA adapter configuration register
0175 541 : EXE$GB_CPUYPE - Index specifying what CPU we are executing on
0175 542 : ** Assumes all drivers use DATAPATH 1 **
0175 543 :
0175 544 : OUTPUT PARAMETERS:
0175 545 :
0175 546 : R0 - LBS -> Success
0175 547 : LBC -> Failure
0175 548 :
0175 549 : R1,R2,R4 - Destroyed
0175 550 : All other registers preserved
0175 551 :
0175 552 :--
0175 553
0175 554 BOOS$PURDPR:
0175 555
50 01 3C 0175 556 MOVZWL #SS$ NORMAL,R0 : Assume success
0178 557 CPUDISP <<780,100$>,- : Dispatch on EXE$GB_CPUYPE
0178 558 <<750,200$>,-
0178 559 <<730,300$>,-
0178 560 <<790,100$>,-
0178 561 <<UV1,170$>>,- : Nothing to do for Micro-VAX I
0178 562 ENVIRON=VMB;
01AB 563
01AB 564 100$:
62 52 44 A3 DE 01AB 565 MOVAL UBASL DPR+4(R3),R2 : CPU type 11/780 and 11/790:
0178 566 ASHL #UBASV DPR_BNE,#1,(R2) : Get Datapath Register address
62 01 1F 78 01AF 567 MOVL (R2),R1 : Purge datapath
09 51 62 DO 01B3 568 BBC #UBASV DPR_XMTER,R1,170$ : Get Datapath register contents
62 01 1E E1 01B6 569 ASHL #UBASV DPR_XMTER,#1,(R2) : Branch if no error
50 01F4 8F 78 01BA 570 150$: MOVZWL #SS$_PARITY,R0 : Clear error in datapath
05 01C3 571 170$: RSB : Set failure status
0178 572 : Return to caller
0178 573 200$: MOVAL UBISL DPR+4(R3),R2 : CPU type 11/750, Datapath Register
62 52 04 A3 DE 01C4 574 ASHL #UBISV DPR_PUR,#1,(R2) : Purge Datapath
0178 575 MOVL #UBISC_PURCNT,R4 : Get max # of tries for
62 01 00 78 01C8 576 : purge done test
54 0A DO 01CC 577 230$: MOVL (R2),R1 : Get datapath register contents
05 51 62 DO 01CF 578 BBC #UBISV DPR_PUR,R1,250$ : Branch if purge done
05 51 00 E1 01D2 579 SOBGTR R4,230$ : Branch if more tries allowed
F6 54 F5 01D6

```



```

      04 11 01D9 580      BRB 270$      ; Return failure status
E4 51 1F E1 01DB 581 250$: BBC #UBISV DPR_ERROR,R1,170$ ; Branch if no purge error
      62 00 D2 01DF 582 270$: MCOML #0,(R2) ; Clear datapath error(s)
      DA 11 01E2 583      BRB 150$      ; Return with failure status
      01E4 584
      51 10 A3 D0 01E4 585 300$: MOVL UBISL_SR(R3),R1 ; Get Unibus Error Summary Register
      01E8 586      ; Nebula
51 8001C000 8F D3 01E8 587      BITL #<UBISM_SR_UWE!- ; Any UB errors? (write error,
      01EF 588      UBISM_SR_MRPE!- ; map parity error,
      01EF 589      UBISM_SR_NXM!- ; non-existent memory,
      01EF 590      UBISM_SR_UCE>,R1 ; or uncorrected read error.)
      D2 13 01EF 591      BEQL 170$ ; Branch if no errors
      01F1 592 ; ***** QUESTION - Is there anything to do to clear the error status?
      CB 11 01F1 593      BRB 150$      ; Return failure status
      01F3 594

```

```

000001F4 01F3 596 .ALIGN LONG ; Alignment needed by some drivers!!!
000001F4 01F4 597 BOO$QIOSIZ=-BOO$AL_VECTOR ; Size of boot QIO routine
000001F4 01F4 598 ;
000001F4 01F4 599 BOO$DRIVER==. ; Start of boot driver (after
000001F4 01F4 600 ; it's been moved)
000001F4 01F4 601 ; NOTE: Boot drivers must be in
000001F4 01F4 602 ; psect BOOTDRIVR_2
00000000 0000 603
00000000 0000 604 .PSECT BOOTDRIVR_3
00000000 0000 605
00000000 0000 606 BOO$DRIVER_TBL=. ; Boot driver table
00000000 0000 607
00000000 0000 608 .PSECT BOOTDRIVR_5
00000000 0000 609
00000000 0000 610 .LONG 0 ; End of boot driver table
00000000 0004 611
00000000 0000 612 .PSECT BOOTDRIVR_6

```



```

0000 614 .SBTTL BOO$SELECT - Select boot driver
0000 615
0000 616 :++
0000 617 : FUNCTIONAL DESCRIPTION:
0000 618 :
0000 619 : This routine is called the first time BOO$QIO calls a driver.
0000 620 : It searches the boot driver table to locate the proper driver.
0000 621 : The correct linkage is made in BOO$AL_VECTOR.
0000 622 : RPB$L_IOVECSZ is also stored with the size of BOO$QIO plus
0000 623 : the size of the driver. The driver is then jumped to.
0000 624 :
0000 625 : CALLING SEQUENCE:
0000 626 :
0000 627 : JSB BOO$SELECT (Actually called through self-relative
0000 628 : vector in BOO$AL_VECTOR+BOO$L_SELECT)
0000 629 :
0000 630 : INPUT PARAMETERS:
0000 631 :
0000 632 : R9 Address of the RPB
0000 633 :
0000 634 : OUTPUT PARAMETERS:
0000 635 :
0000 636 : None
0000 637 :
0000 638 :--
0000 639 :
0000 640 BOO$SELECT:
007E 8F BB 0000 641 PUSH R1,R2,R3,R4,R5,R6
0000 642 BSBB BOO$RESELECT ; Select the correct driver
007E 8F BA 0006 643 POP R1,R2,R3,R4,R5,R6
000A 644 :
000A 645 : Set up driver vector and jump to driver.
000A 646 :
50 34 A9 D0 000A 647 MOVL RPB$L_IOVEC(R9),R0 ; Get address of vectors
08 B040 17 000E 648 JMP @BOO$L_SELECT(R0)[R0] ; Jump to driver

```

```

0012 650 .SBTTL BOO$MOVE - Select and move boot driver
0012 651
0012 652 :++
0012 653 : FUNCTIONAL DESCRIPTION:
0012 654 :
0012 655 : This routine is called after VMB is finished with a driver.
0012 656 : It searches the boot driver table to locate the proper driver.
0012 657 : The correct linkage is made in BOO$AL_VECTOR and driver moved.
0012 658
0012 659 : CALLING SEQUENCE:
0012 660 :
0012 661 : JSB BOO$MOVE (Actually called through self-relative
0012 662 : vector in BOO$AL_VECTOR+BOO$SL_MOVE)
0012 663
0012 664 : INPUT PARAMETERS:
0012 665 :
0012 666 : R9 Address of the RPB
0012 667
0012 668 : OUTPUT PARAMETERS:
0012 669 :
0012 670 : None
0012 671
0012 672 :--
0012 673
0012 674 BOO$MOVE:
0012 675 PUSHR #^M<R1,R2,R3,R4,R5,R6,R7> ; Save registers
0012 676 BSBB BOO$RESELECT ; Select the correct driver
0012 677 MOVAB @BDT$L_ADDR(R5)[R5],R6 ; Address of current position
0012 678 MOVAB W^BOO$DRIVER,R4 ; Address of new position
0012 679 SUBL3 R4,R6,R7 ; Offset
0012 680 BEQL 20$ ; None, so don't move
0012 681 MOVCL BDT$L_SIZE(R5),(R6),(R4) ; Move driver
0012 682 MOVAB W^BOO$AL_VECTOR,R4
0012 683 SUBL2 R7,BQO$SL_SELECT(R4) ; Adjust offset
0012 684 SUBL2 R7,BQO$SL_DRIVNAME(R4)
0012 685 TSTL BQO$SL_AUXDRNAME(R4) ; Is there one?
0012 686 BEQL 10$ ; No, don;t mess
0012 687 SUBL2 R7,BQO$SL_AUXDRNAME(R4)
0012 688 10$: TSTL BQO$SL_UNIT_INIT(R4) ; Is there one?
0012 689 BEQL 20$ ; No, don;t mess
0012 690 SUBL2 R7,BQO$SL_UNIT_INIT(R4)
0012 691 20$: TSTL BQO$SL_UNIT_DISC(R4) ; Is there one?
0012 692 BEQL 30$ ; No, don;t mess
0012 693 SUBL2 R7,BQO$SL_UNIT_DISC(R4)
0012 694 30$: TSTL BQO$SL_DEVNAME(R4) ; Is there one?
0012 695 BEQL 40$ ; No, don;t mess
0012 696 SUBL2 R7,BQO$SL_DEVNAME(R4)
0012 697 40$: POPR #^M<R1,R2,R3,R4,R5,R6,R7>
0012 698 RSB
0012 699
0012 700 BOO$RESELECT:
0012 701 MOVAL W^BOO$DRIVER_TBL,R5 ; Get address of boot driver table
0012 702 MOVZBL RPB$B_DEVTYPE(R9),R3 ; Get value of boot device type
0012 703 MOVZBL W^EXE$GB_CPUYPE,R4 ; Get cpu type
0012 704 MOVZWL #<BOO$DRIVER-BOO$AL_VECTOR>,R6 ; Compute offset to driver table
0012 705 :
0012 706 : Determine if next driver in table is the correct one.

```



```

      0076 707
50 65 32 0076 708 10$: CVTWL BDT$$_CPUTYPE(R5),R0 : Get cpu type from table
      7B 13 0079 709 : BEQL 400$ : End of table
      05 19 007B 710 : BLSS 20$ : Driver doesn't care about cpu type
54 50 D1 007D 711 : CMPL R0,R4 : Cpu types match?
      17 12 0080 712 : BNEQ 40$ : No, try next driver
      0082 713
50 02 A5 32 0082 714 20$: CVTWL BDT$$_DEVTYPE(R5),R0 : Get boot device type from table
      05 19 0086 715 : BLSS 30$ : Driver doesn't care about device type
53 50 D1 0088 716 : CMPL R0,R3 : Device types match?
      0C 12 008B 717 : BNEQ 40$ : No, try next driver
      008D 718
50 04 A5 D0 008D 719 30$: MOVL BDT$$_ACTION(R5),R0 : Get action routine offset from table
      0F 13 0091 720 : BEQL 60$ : No action routine, this is the driver
      6540 16 0093 721 : JSB (R5)[R0] : Call action routine
      09 50 E8 0096 722 : BLBS R0,60$ : Branch if this is the driver
56 08 A5 C0 0099 723 40$: ADDL BDT$$_SIZE(R5),R6 : Account for this driver's size
      55 28 C0 009D 724 : ADDL #BDT$$_LENGTH,R5 : Point to next driver entry
      D4 11 00A0 725 : BRB 10$ : Try next driver
      00A2 726
      00A2 727 : Have the right driver. R5 points to driver table entry. R6 contains
      00A2 728 : accumulated offset from IOVEC to the start of the driver. Update
      00A2 729 : pertinent entries in the IOVEC.
      00A2 730
54 0000'CF DE 00A2 731 60$: MOVAL W*BOOSAL VECTOR,R4 : Cover the vector
      000001F4 8F C1 00A7 732 : ADDL3 #BOOSQIOSIZ,- : Add boot QIO size to
      08 A5 00AD 733 : BDT$$_SIZE(R5),- : driver size
      38 A9 00AF 734 : RPB$$_IOVECSZ(R9) : and store in RPB
10 A5 56 C1 00B1 735 : ADDL3 R6,BDT$$_ENTRY(R5),- : Calc offset to driver
      08 A4 00B5 736 : BQOSL_SELECT(R4) : entry point and store in vector
14 A5 56 C1 00B7 737 : ADDL3 R6,BDT$$_DRVRNAME(R5),- : Calc offset to driver
      0C A4 00BB 738 : BQOSL_DRVRNAME(R4) : name and store in vector
      1C A4 D4 00BD 739 : CLRL BQOSL_UNIT_INIT(R4) : Assume none
51 1C A5 D0 00C0 740 : MOVL BDT$$_UNIT_INIT(R5),R1 : Pick up possible UNIT_INIT entry
      05 13 00C4 741 : BEQL 70$ : None specified, default to a RET
1C A4 51 56 C1 00C6 742 : ADDL3 R6,R1,BQOSL_UNIT_INIT(R4) : Calc offset to driver
      00CB 743 : UNIT_INIT point and store in vector
      00CB 744 70$: CLRL BQOSL_AUXDRNAME(R4) : Assume none
51 20 A4 D4 00CE 745 : MOVL BDT$$_AUXDRNAME(R5),R1 : Pick up possible driver name
      18 A5 D0 00D2 746 : BEQL 80$ : None specified, default to a zero
20 A4 51 56 C1 00D4 747 : ADDL3 R6,R1,BQOSL_AUXDRNAME(R4) : Calc offset to driver
      00D9 748 : auxiliary name and store in vector
      00D9 749 80$: CLRL BQOSL_UNIT_DISC(R4) : Assume none
51 20 A5 D0 00DC 750 : MOVL BDT$$_UNIT_DISC(R5),R1 : Pick up possible UNIT_DISC entry
      05 13 00E0 751 : BEQL 90$ : None specified, default to a zero
2C A4 51 56 C1 00E2 752 : ADDL3 R6,R1,BQOSL_UNIT_DISC(R4) : Calc offset to driver
      00E7 753 : UNIT_DISC point and store in vector
      00E7 754 90$: CLRL BQOSL_DEVNAME(R4) : Assume none
51 30 A4 D4 00EA 755 : MOVL BDT$$_DEVNAME(R5),R1 : Pick up possible device name
      24 A5 D0 00EE 756 : BEQL 100$ : None specified, default to a zero
30 A4 51 56 C1 00F0 757 : ADDL3 R6,R1,BQOSL_DEVNAME(R4) : Calc offset to device
      00F5 758 : name and store in vector
      05 00F5 759 100$: RSB
      00F6 760
      00F6 761 :
      00F6 762 : No driver in the driver table accepted this QIO
      00F6 763 :

```

BOOTDRIVR  
V04-000

F 5  
DISPATCHER FOR BOOTSTRAP I/O DRIVERS  
BOOS\$MOVE - Select and move boot driver

15-SEP-1984 23:40:28 VAX/VMS Macro V04-00  
4-SEP-1984 23:02:48 [BOOTS.SRC]BOOTDRIVR.MAR;1

Page 19  
(9)

00 00F6 764 400\$: HALT  
00F7 765  
00F7 766 .END



BOOTDRVR  
Symbol table

DISPATCHER FOR BOOTSTRAP I/O DRIVERS<sup>5</sup>

15-SEP-1984 23:40:28 VAX/VMS Macro V04-00  
4-SEP-1984 23:02:48 [BOOTS.SRC]BOOTDRVR.MAR;1

Page 20  
(9)

\$\$BASE	= 00000001		
\$\$DISPL	= 00000008		
\$\$GENSW	= 00000001		
\$\$HIGH	= 00000007		
\$\$LIMIT	= 00000006		
\$\$LOW	= 00000001		
\$\$MNSW	= 00000001		
\$\$MXSW	= 00000001		
BDTSK_LENGTH	= 00000028		
BDTSL_ACTION	00000004		
BDTSL_ADDR	0000000C		
BDTSL_AUXDRNAME	00000018		
BDTSL_CPUTYPE	00000000		
BDTSL_DEVNAME	00000024		
BDTSL_DEVTYPE	00000002		
BDTSL_DRVRNAME	00000014		
BDTSL_ENTRY	00000010		
BDTSL_SIZE	00000008		
BDTSL_UNIT_DISC	00000020		
BDTSL_UNIT_INIT	0000001C		
BOOSAC_VECTOR	00000000	RG	02
BOOSDRIVER	= 000001F4	RG	02
BOOSDRIVER_TBL	= 00000000	R	03
BOOSGB_UMR_DP	00000038	RG	02
BOOSGL_UCODE	00000028	RG	02
BOOSGL_UMR_DIS	00000024	RG	02
BOOSGL_UMR_TMPL	00000034	RG	02
BOOSMAP	0000011D	RG	02
BOOSMOVE	00000012	R	05
BOOSPURDPR	00000175	R	02
BOOSQIO	00000046	RG	02
BOOSQIOSIZ	= 000001F4		
BOOSRESELECT	00000063	R	05
BOOSSELECT	00000000	R	05
BQOSB_CPUTYPE	= 00000039		
BQOSB_UMR_DP	= 00000038		
BQOSL_AUXDRNAME	= 00000020		
BQOSL_CPUDATA	= 0000003A		
BQOSL_DEVNAME	= 00000030		
BQOSL_DRVRNAME	= 0000000C		
BQOSL_SELECT	= 00000008		
BQOSL_TENUSEC	= 0000003E		
BQOSL_UBDELAY	= 00000042		
BQOSL_UCODE	= 00000028		
BQOSL_UMR_DIS	= 00000024		
BQOSL_UMR_TMPL	= 00000034		
BQOSL_UNIT_DISC	= 0000002C		
BQOSL_UNIT_INIT	= 0000001C		
BQOSW_VERSION	= 00000010		
BTDSK_HSCCI	= 00000020		
BUF	= 00000004		
COMPUTE_PFN	00000097	R	02
ERROUT	*****	X	02
EXESGB_CPUDATA	0000003A	RG	02
EXESGB_CPUTYPE	00000039	RG	02
EXESGL_TENUSEC	0000003E	RG	02
EXESGL_UBDELAY	00000042	RG	02

FILLSPT	= 00000167	R	02
FUNC	= 00000010		
INIT_MAPREGS	= 0000008C	R	02
LBN	= 0000000C		
MBASL_MAP	= 00000800		
MODE	= 00000014		
NDTS_UBO	= 00000028		
OPS_ACB	= 0000006F		
OPS_ACBF	= 0000004F		
OPS_ACBG	= 00004FFD		
OPS_ACBH	= 00006FFD		
OPS_ADDD2	= 00000060		
OPS_ADDD3	= 00000061		
OPS_ADDF2	= 00000040		
OPS_ADDF3	= 00000041		
OPS_ADDG2	= 000040FD		
OPS_ADDG3	= 000041FD		
OPS_ADDH2	= 000060FD		
OPS_ADDH3	= 000061FD		
OPS_ADDP4	= 00000020		
OPS_ADDP6	= 00000021		
OPS_ASHP	= 000000F8		
OPS_CLRD	= 0000007C		
OPS_CLRF	= 000000D4		
OPS_CLRG	= 0000007C		
OPS_CLRH	= 00007CFD		
OPS_CMPD	= 00000071		
OPS_CMPF	= 00000051		
OPS_CMPG	= 000051FD		
OPS_CMPH	= 000071FD		
OPS_CMPP3	= 00000035		
OPS_CMPP4	= 00000037		
OPS_CRC	= 0000000B		
OPS_CVTBD	= 0000006C		
OPS_CVTBF	= 0000004C		
OPS_CVTBG	= 00004CFD		
OPS_CVTBH	= 00006CFD		
OPS_CVTDB	= 00000068		
OPS_CVTDF	= 00000076		
OPS_CVTDH	= 000032FD		
OPS_CVTDL	= 0000006A		
OPS_CVTDW	= 00000069		
OPS_CVTFB	= 00000048		
OPS_CVTFD	= 00000056		
OPS_CVTFG	= 000099FD		
OPS_CVTFH	= 000098FD		
OPS_CVTFL	= 0000004A		
OPS_CVTFW	= 00000049		
OPS_CVTGB	= 000048FD		
OPS_CVTGF	= 000033FD		
OPS_CVTGH	= 000056FD		
OPS_CVTGL	= 00004AFD		
OPS_CVTGW	= 000049FD		
OPS_CVTHB	= 000068FD		
OPS_CVTHD	= 0000F7FD		
OPS_CVTHF	= 0000F6FD		
OPS_CVTHG	= 000076FD		

BOOTDRIVR  
Symbol table

DISPATCHER FOR BOOTSTRAP I/O DRIVERS<sup>H 5</sup>

15-SEP-1984 23:40:28 VAX/VMS Macro V04-00  
4-SEP-1984 23:02:48 [BOOTS.SRC]BOOTDRIVR.MAR;1

Page 21  
(9)

OPS\_CVTHL = 00006AFD  
OPS\_CVTHW = 000069FD  
OPS\_CVTLD = 0000006E  
OPS\_CVTLF = 0000004E  
OPS\_CVTLG = 00004EFD  
OPS\_CVTLM = 00006EFD  
OPS\_CVTLP = 000000F9  
OPS\_CVTPL = 00000036  
OPS\_CVTPS = 00000008  
OPS\_CVTPT = 00000024  
OPS\_CVTRDL = 0000006B  
OPS\_CVTRFL = 0000004B  
OPS\_CVTRGL = 00004BFD  
OPS\_CVTRHL = 00006BFD  
OPS\_CVTSP = 00000009  
OPS\_CVTTP = 00000026  
OPS\_CVTWD = 0000006D  
OPS\_CVTWF = 0000004D  
OPS\_CVTWG = 00004DFD  
OPS\_CVTWH = 00006DFD  
OPS\_DIVD2 = 00000066  
OPS\_DIVD3 = 00000067  
OPS\_DIVF2 = 00000046  
OPS\_DIVF3 = 00000047  
OPS\_DIVG2 = 000046FD  
OPS\_DIVG3 = 000047FD  
OPS\_DIVH2 = 000066FD  
OPS\_DIVH3 = 000067FD  
OPS\_DIVP = 00000027  
OPS\_EDITPC = 00000038  
OPS\_EMODD = 00000074  
OPS\_EMODF = 00000054  
OPS\_EMODG = 000054FD  
OPS\_EMODH = 000074FD  
OPS\_MATCHC = 00000039  
OPS\_MNEGD = 00000072  
OPS\_MNEGF = 00000052  
OPS\_MNEGG = 000052FD  
OPS\_MNEGH = 000072FD  
OPS\_MOVD = 00000070  
OPS\_MOVF = 00000050  
OPS\_MOVEG = 000050FD  
OPS\_MOVEH = 000070FD  
OPS\_MOVEP = 00000034  
OPS\_MOVEC = 0000002E  
OPS\_MOVEUC = 0000002F  
OPS\_MULD2 = 00000064  
OPS\_MULD3 = 00000065  
OPS\_MULF2 = 00000044  
OPS\_MULF3 = 00000045  
OPS\_MULG2 = 000044FD  
OPS\_MULG3 = 000045FD  
OPS\_MULH2 = 000064FD  
OPS\_MULH3 = 000065FD  
OPS\_MULP = 00000025  
OPS\_POLYD = 00000075  
OPS\_POLYF = 00000055

OPS\_POLYG = 000055FD  
OPS\_POLYH = 000075FD  
OPS\_SCANC = 0000002A  
OPS\_SKPC = 0000003B  
OPS\_SPANC = 0000002B  
OPS\_SUBD2 = 00000062  
OPS\_SUBD3 = 00000063  
OPS\_SUBF2 = 00000042  
OPS\_SUBF3 = 00000043  
OPS\_SUBG2 = 000042FD  
OPS\_SUBG3 = 000043FD  
OPS\_SUBH2 = 000062FD  
OPS\_SUBH3 = 000063FD  
OPS\_SBP4 = 00000022  
OPS\_SBP6 = 00000023  
OPS\_TSTD = 00000073  
OPS\_TSTF = 00000053  
OPS\_TSTG = 000053FD  
OPS\_TSTH = 000073FD  
PRS\_MAPEN = 00000038  
PRS\_POBR = 00000008  
PRS\_SID\_TYP730 = 00000003  
PRS\_SID\_TYP750 = 00000002  
PRS\_SID\_TYP780 = 00000001  
PRS\_SID\_TYP790 = 00000004  
PRS\_SID\_TYPUV1 = 00000007  
PTESC\_KQ = 10000000  
PTESM\_PFN = 001FFFFFFF  
PTESM\_VALID = 80000000  
PUSH\_RETRY = 000000F3  
RPB = 0000000C  
RPBSB\_DEVTYP = 00000066  
RPBSL\_ADPPHY = 0000005C  
RPBSL\_ADPVIR = 00000060  
RPBSL\_CSRPHY = 00000054  
RPBSL\_CSRVIR = 00000058  
RPBSL\_IOVEC = 00000034  
RPBSL\_IOVECSZ = 00000038  
RPBSL\_SVASPT = 00000050  
RPBSW\_BOOTNDT = 000000A1  
SIZE = 00000008  
SSS\_NORMAL = 00000001  
SSS\_PARITY = 000001F4  
SVASPT = 00000004  
UBASL\_DPR = 00000040  
UBASL\_MAP = 00000800  
UBASM\_MAP\_VALID = 80000000  
UBASV\_DPR\_BNE = 0000001F  
UBASV\_DPR\_XMTER = 0000001E  
UBASV\_MAP\_BO = 00000019  
UBASV\_MAP\_DPD = 00000015  
UBISC\_PURENT = 0000000A  
UBISL\_DPR = 00000000  
UBISL\_MAP = 00000800  
UBISL\_SR = 00000010  
UBISM\_SR\_MRPE = 00008000  
UBISM\_SR\_NXM = 00010000

R 02



BOOTDRIVR  
Symbol table

DISPATCHER FOR BOOTSTRAP I/O DRIVERS<sup>1 5</sup>

15-SEP-1984 23:40:28  
4-SEP-1984 23:02:48

VAX/VMS Macro V04-00  
[BOOTS.SRC]BOOTDRIVR.MAR;1

Page 22  
(9)

UBISM\_SR\_UCE = 80000000  
UBISM\_SR\_UWE = 00004000  
UBISV\_DPR\_ERROR = 0000001F  
UBISV\_DPR\_PUR = 00000000  
VASS\_BYTE = 00000009  
VASS\_VPN = 00000015  
VASV\_BYTE = 00000000  
VASV\_SYSTEM = 0000001F  
VASV\_VPN = 00000009  
VABASE = 00000008  
VMB\_VERSION = 0000000D

+-----+  
! Psect synopsis !  
+-----+

PSECT name	Allocation	PSECT No.	Attributes
. ABS .	00000000 ( 0.)	00 ( 0.)	NOPIC USR CON ABS LCL NOSHR NOEXE NORD NOWRT NOVEC BYTE
\$ABSS\$	00000028 ( 40.)	01 ( 1.)	NOPIC USR CON ABS LCL NOSHR EXE RD WRT NOVEC BYTE
BOOTDRIVR_1	000001F4 ( 500.)	02 ( 2.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC LONG
BOOTDRIVR_3	00000000 ( 0.)	03 ( 3.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC BYTE
BOOTDRIVR_5	00000004 ( 4.)	04 ( 4.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC BYTE
BOOTDRIVR_6	000000F7 ( 247.)	05 ( 5.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC BYTE

+-----+  
! Performance indicators !  
+-----+

Phase	Page faults	CPU Time	Elapsed Time
Initialization	29	00:00:00.09	00:00:00.33
Command processing	108	00:00:00.80	00:00:02.74
Pass 1	627	00:00:23.76	00:00:48.10
Symbol table sort	0	00:00:02.72	00:00:05.54
Pass 2	161	00:00:05.84	00:00:11.03
Symbol table output	28	00:00:00.23	00:00:00.78
Psect synopsis output	3	00:00:00.03	00:00:00.04
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	958	00:00:33.47	00:01:08.57

The working set limit was 2000 pages.  
114533 bytes (224 pages) of virtual memory were used to buffer the intermediate code.  
There were 100 pages of symbol table space allocated to hold 1738 non-local and 39 local symbols.  
3518 source lines were read in Pass 1, producing 20 object records in Pass 2.  
157 pages of virtual memory were used to define 154 macros.

+-----+  
! Macro library statistics !  
+-----+

Macro library name

Macros defined

-----  
\$255\$DUA28:[BOOTS.OBJ]BOOTS.MLB;1  
\$255\$DUA28:[SYS.OBJ]LIB.MLB;1  
\$255\$DUA28:[SYSLIB]STARLET.MLB;2  
TOTALS (all libraries)

-----  
0  
11  
8  
19

1889 GETS were required to define 19 macros.

There were no errors, warnings or information messages.

MACRO/LIS=LIS\$:BOOTDRIVR/OBJ=OBJ\$:BOOTDRIVR MASD\$:[EMULAT.SRC]MISSING/UPDATE=(MASD\$:[EMULAT.ENH]MISSING)+MASD\$:[BOOTS.SRC]BOOTDRIVR/



0037 AH-BT13A-SE  
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION  
CONFIDENTIAL AND PROPRIETARY

